

## CSG - 11700 Series Full Height Turnstile



### PRODUCT OVERVIEW

The CSG Turnstile range are designed and manufactured for controlling access in environments such as reception areas, health clubs, theme parks, public buildings and stadiums.

Suitable for outdoor use, the CSG turnstile range come in the form of single or double according to your requirements. This also extends to varying heights of turnstile again tailored to suit your needs.

### CONSTRUCTION FEATURES

Available with straight arm as standard or optional trombone. The turnstiles are available as 4 wing 90° rotation to prevent 'Crowd Loading' or 3 Wing 120° rotation for faster throughput.

- Bi-directional control, fail safe or fail secure
- Factory settings need no adjustment.
- Can handle high traffic volumes
- Helps employ strict security standards
- Can function in severe operating conditions
- Interior & exterior installations
- 100% - capable of continuous usage

### CONTACT US

Call us on +44 (0) 1293 553888

Email us [sales@covasecuritygates.com](mailto:sales@covasecuritygates.com)

### DIMENSIONS

Single: 1480mm X 1410mm X 2350mm

Double: 2220mm X 1500mm X 2350mm

Rotor: 76mm Ø tube with bottom support bearing

Arms: 42mm Ø tube with capped ends

Side frames: 33mm Ø tube welded to curve base plate

Contact CSG for a bespoke solution if required.

### FINISH

All turnstiles are available in a wide range of finishes ranging from:

- 316 Stainless Steel.
- Polyester powder coated to a specific RAL No.
- Galvanised Steel.

# CSG 11700 Series - Full Height Turnstile

The CSG Turnstile range is a diverse dynamic range which is flexible and tailor made to provide you with the best solution to control pedestrian access.

Manufactured to the highest standards our heavy duty turnstiles are complete in all respects. Designed to give years of continuous use under the most arduous conditions.

In the event of a power failure all Turnstiles are fitted with a manual over-ride facility. A unique trap proof design prevents users becoming trapped in a 45 degree position.

The turnstiles may be operated by simple stand-alone access control readers through to complex time and attendance systems. They are an ideal solution in terms of security, all of the range can also be combined with a large range of access control.

## FLOW RATE

F15 to 22 /min in a single direction

## ELECTRICAL SUPPLY

Mains Supply: 230V 50Hz single phase rated @ 10 Amp



**If required, please contact CSG for a bespoke solution.**

### Cova Security Gates Ltd

Unit C1, Sussex Manor Business Park  
Crawley, West Sussex, RH10 9NH, UK  
[covasecuritygates.com](http://covasecuritygates.com)

✉ [sales@covasecuritygates.com](mailto:sales@covasecuritygates.com)

☎ +44(0)1293 553 888

📱 @CovaSecurityUK

📍 Cova Security Gates Ltd

